

BLUEDEALS%

100 cut-off wheels with diameter 125 mm for steel and INOX in a handy transport case.

Only available during the promotional period from 1 September to 31 December 2024

Cut-off wheel EHT 125-1.0 START STEELOX

Promotional period: 1 September to 31 December 2024



High performance at a great price:

The START range of cut-off wheels offers reliable **PFERD** quality for trade and assembly work. This means you can achieve reliable results at attractive purchase costs.

The thin cut-off wheel EHT 125-1.0 START

STEELOX offers good cutting performance and a good tool life and is now available as a set of 100 in a handy plastic transport case with handle.


The benefits to you from the START range:

- Suitable for general use on steel and stainless steel (INOX).
- Fast work progress thanks to good cutting performance.
- High economic efficiency due to good tool life.

The benefits to you from thin cut-off wheels:

- Thin cuts with minimized burr formation.
- Convenient and safe.
- Fast cutting.
- Thin cut-off wheels are ideal for cordless angle grinders.







PFERDEFFICIENCY recommends thin cut-off wheels to achieve perfect results as quickly as

Subject to technical modifications.

06/2024

819 116

Printed in Germany.



EHT 125-1.0 START STEELOX

Contents:

possible.

The set contains 100 EHT 125-1.0 START STEELOX cut-off wheels in a handy plastic transport case with handle.

Special features:

The handy plastic transport case protects the tools against dirt and damage.

| D [mm] | T/U [mm] | H [mm] | Max. RPM | Abrasive | | ltem no. | Designation |
|---------------|--------------|-----------|----------|----------|-----|----------|------------------------------------|
| Flat design E | EHT (shape 4 | 1) | | | | | |
| 125 | 1 | 22.23 | 12,200 | А | 100 | 69902459 | EHT 125-1,0 START STEELOX BLUEDEAL |

Offers valid while stocks last. Only available from participating retailers. Subject to errors and change without notice.





2

www.pferd.com · info@pferd.com

PFERD quality is certified according to ISO 9001

ts the